

CABLE DRUM TRAILERS



FEATURES

STANDARD

Heavy Duty Steel Construction
Hydraulic Hand Pump
Spindle with 2 fixing clamps
Lighting System

OPTIONAL

Petrol Engine
Rubber Driving Rolle

Technical Data	UT	ECT 1003	ECT 1006	ECT 1010
Drum Diameter Max	mm	2500	3200	3500
Drum Width Max	mm	1300	1700	2000
Spindle Diameter	mm	60-Solid	70-Solid	90-Solid
Clear Width	mm	1580	2000	2300
Overall Length	mm	3100	4000	4150
Overall Width	mm	2300	2900	3370
Drum Diameter Min	mm	1060	2000	2300
Payload	Ton	3	6	10
Max. Speed	km/h	40	24	24
Dead Weight	kg	750	1300	1400
Total Weight	kg	3750	7300	11400
Coupling Height	mm	610	820	820
Towing Eye	mm	30	42	54
Overall Height(Unloaded)	mm	1800	2200	2200
Tyres		8.5R 17.5 PR	12R 20 18PR	14R 20 20PR
Drum Lift- Hyd System	Two Single Acting Rams Operated Individually via two isolating Ball Valves, Hand Pump, Reservoir. While ordering add suffix-PE for Petrol Engine Drive.			
Finish	RAL 2004			