

16F Fiber Optic Inline Closure

HTSC-141A

FEATURES

- ~ Installation and re-entry with minimum of tools
- ~ Easy to be opened and closed
- ~ Re-enterable and reusable
- ~ All hardware is captivated
- ~ Capable of loading 1:8, 1:16 PLC splitter
- ~ Max capacity: **16 SC adapters**

OPTIONAL ACCESSORIES

- ~ Duct mounting kits
- ~ Pole mounting kits
- ~ Pressure valve
- ~ Grounding device

COMPONENTS

- ~ Cover
- ~ Bottom
- ~ Seal gasket
- ~ Clamp
- ~ Splice Tray (with heat shrink sleeves)
- ~ Cable fixing device
- ~ Grounding wire
- ~ Nylon tie
- ~ Labeling paper
- ~ Buffer Tube
- ~ Installation tape

APPLICATION

- ~ Duct Mounting, Pole Mounting, Underground, Wall Mounting.



Main Port Drop Ports Main Port

SPECIFICATIONS

Model No.	HTSC-141A
Size (L x W x H)	305mm x 216mm x 107mm
Spliced Fiber Capacity	Standard fiber 16 splices
Adapter	Max. 16 SC adapter
Cable Ports	Main cables : 4 ports Drop cables : 16 ports
Max. Cable Diameter	Main cables : 12mm Drop cables : 3mm / 3x2mm