

## **144F Fiber Optic Splice Closures**

6 Trays, 6×24 Fibers



## **FEATURES**

- May be used for cut, uncut and taut sheath applications.
- May be used for all fiber optic cable.
- Sheath retention & central strength member fasten system included.
- Closure construction and lightweight plastic provides strength and resistance to chemical and U.V attack.
- Installation and reentry with a minimum of tools.
- All hardware are included.
- Protection class: IP68.
- RoHS compliance.





## APPLICATION











## **SPECIFICATIONS**

| Model No.                      | YT01061   SSC-450175-4P-144-6T/7T-T204B<br>450×175m, 144 Fibers Capacity, 6 Trays, 4 Port, Enclosure , w/o Mounting Kits |
|--------------------------------|--|
| Spliced Fiber Storage Capacity | 144 splices (6×24)   |
| Size   Height x Diameter       | 450mm x 175mm (w/o clamp), 450mm x 230mm (w/ clamp)  |
| Cable Ports                    | 1 oval port (24mm), 4 round ports (17.5mm)   |

| Model No. | Madal Na  | Wall Mounting Kit - 1   Wall Mounting Kit - 2   Wall Mounting Kit - 3 |
|-----------|---|---|
|           | Pole Mounting Kit - 1   Pole Mounting Kit - 2   Pole Mounting Kit - 3 |   |